

**Batteries & Runtime**

Battery Type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Battery mounting	Stand alone battery stack
Expected Battery Life	3 - 5
RBC Quantity	2
Battery blocks per string	--
Battery Volt-Amp-Hour Capacity	1920

**Physical**

Maximum Height	5.1inches ( 130mm , 13.0cm )
Maximum Width	17.0inches ( 432mm , 43.2cm )
Maximum Depth	26.88inches ( 682mm , 68.27cm )
Rack Height	3U
Net Weight	200.2lbs. ( 91.0kg )
Shipping Weight	232.1lbs. ( 105.5kg )
Shipping Height	16.54inches ( 420mm , 42.0cm )
Shipping Width	23.63inches ( 600mm , 60.0cm )
Shipping Depth	39.38inches ( 1000mm , 100.0cm )
Color	Black
Units per Pallet	1.0

**Environmental**

Operating Environment	32 - 104 °F ( 0 - 40 °C )
Operating Relative Humidity	0 - 95% no %
Operating Elevation	0-10000ft ( 0-3000meters )
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95% no %
Storage Elevation	0-50000ft ( 0-15000meters )

**Conformance**

Approvals	OSHDPD
Standard Warranty	2 years repair or replace

**Sustainable Offer Status**

RoHS	Compliant
REACH	REACH: Contains No SVHCs