

**Batteries & Runtime**

| | |
|-------------------------------|--|
| Battery Type | Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof |
| Battery Mounting | Stand alone battery stack |
| Expected Battery Life (years) | 3 - 5 |
| RBC Quantity | 2 |
| Battery blocks per string | -- |

Physical

| | |
|------------------|----------------------------------|
| Maximum Height | 5.1inches (130mm , 13.0CM) |
| Maximum Width | 17.0inches (432mm , 43.2CM) |
| Maximum Depth | 26.88inches (682mm , 68.27CM) |
| Rack Height | 3U |
| Net Weight | 200.2lbs. (91.0KG) |
| Shipping weight | 232.1lbs. (105.5KG) |
| Shipping Height | 16.54inches (420mm , 42.0CM) |
| Shipping Width | 23.63inches (600mm , 60.0CM) |
| Shipping Depth | 39.38inches (1000mm , 100.0CM) |
| Color | Black |
| Units per Pallet | 1.0 |

Environmental

| | |
|-----------------------------|-----------------------------|
| Operating Temperature | 32 - 104 °F (0 - 40 °C) |
| Operating Relative Humidity | 0 - 95% no % |
| Operating Elevation | 0-10000ft (0-3000meters) |
| Storage Temperature | -15 - 45 °C |
| Storage Relative Humidity | 0 - 95% no % |
| Storage Elevation | 0-50000ft (0-15000meters) |

Conformance

| | |
|-------------------|---------------------------|
| Approvals | OSHPD |
| Standard Warranty | 2 years repair or replace |

Sustainable Offer Status

| | |
|-------|--------------------------|
| RoHS | Compliant |
| REACH | REACH: Contains No SVHCs |