

Dell Smart-UPS DLT1500RM2UC

Technical Specifications

Batteries & Runtime

Battery Type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Battery Mounting	Stand alone battery stack
Expected Battery Life (years)	4-6
RBC Quantity	1
Battery blocks per string	--

Physical

Maximum Height	3.39 inches (8.6 cm)
Maximum Width	17.0 inches (43.2 cm)
Maximum Depth	18.78 inches (47.7 cm)
Rack Height	2U
Net Weight	58.42 lbs. (26.5 kg)
Shipping weight	70.81 lbs. (32.12 kg)
Shipping Height	9.25 inches (23.5 cm)
Shipping Width	23.23 inches (59 cm)
Shipping Depth	24.02 inches (61.0 cm)
Color	Black
Units per Pallet	8.0

Environmental

Operating Temperature	32 - 104 °F (0 - 40 °C)
Operating Relative Humidity	0 - 95%
Operating Elevation	0-10000ft (0-3000meters)
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95%
Storage Elevation	0-50000ft (0-15000meters)

Conformance

Approvals	OSHPD, cULus, ENERGY STAR V2.0
Standard Warranty	3 years repair or replace

Sustainable Offer Status

RoHS	Compliant
REACH	REACH: Contains No SVHCs